

POWERMERICA (USA)



Made by Powermerica (USA)

SAE 15W-40 CI-4

Powermerica Heavy Duty Synthetic Blend SAE 15W-40 CI-4 Diesel Engine Oil is a premium multi-grade oil specifically engineered to meet the requirements of naturally aspirated, turbocharged, or supercharged diesel, gasoline, and propane engines used in automotive, trucking, construction, mining and farm equipment. It helps extend overall engine life by minimizing sludge and varnish formation and providing outstanding anti-wear protection and deposit control even under the toughest driving conditions.

Powermerica Heavy Duty Synthetic Blend SAE 15W-40 CI-4 Diesel Engine Oil outperforms conventional motor oil and meets or exceeds the American Petroleum Institute (API) CI-4 / SL classifications and all prior API specifications including CH-4, CG-4, CF-4, CF-2, CF and API SJ, and SH. It has been field tested to be comparable to most American, Asian and European manufacturers' standards including Mack EO-M Plus, Cummins CES 20078, Volvo VDS / VDS-2, Caterpillar ECF-1, and power shift transmissions specifying Allison C-3 / C-4, CAT TO-2 and many other OEM's specifications where a heavy duty API CI-4/SL motor oil is recommended.

Benefits and Applications

- For diesel, propane, and gasoline engines
- Exceeds API CI-4 service classification
- Excellent cold-crank capabilities
- Outstanding anti-wear protection

SAE 15W-40 CI-4 Typical Characteristics

Viscosity @ 100°C, cSt	16	(ASTM D445-19)
Viscosity Index (VI)	132	(ASTM D2270-16)
Total Base No. TBN	10	(ASTM D2896-15)
Flash Point, COC °C	220	(ASTM D92-18)
Pour Point, °C	-25	(ASTM D97-11)

Available Packaging

18 Liter; 25 Liter, 208 Liter



<https://www.powermerica.net>