

POWERMERICA (USA)



Made by Powermerica (USA)

SAE 15W-40 CK-4

Powermerica Heavy Duty Synthetic Blend SAE 15W-40 CK-4 Diesel Engine Oil is a high-performance engine oil designed to meet 2017 and newer on-highway and Tier 4 exhaust emission standards. It provides enhanced protection against wear, oxidation, shear viscosity loss, low and high-temperature degradation, soot-related thickening and protection against particulate filter blocking and catalyst poisoning. It outperforms conventional motor oil and is recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane truck, sport utility vehicle, and passenger car engines.

Powermerica Heavy Duty Synthetic Blend SAE 15W-40 CK-4 Diesel Engine Oil meets or exceeds American Petroleum Institute (API) CK-4 / SN and all previous service classifications. It conforms to DFS 93K222 specifications and is Volvo VDS-4.5, Mack EOS-4.5, and Renault VI RLD-3 approved. Furthermore, it has been field tested to be comparable to most American, Asian, and European manufacturers' standards including: ACEA E7-16, ACEA E9-16, FORD WSS-M2C171-F1, MB 228.31, Renault VI RLD-4, CAT ECF-3, KOMATSU and many other OEM's specifications that recommend a synthetic blend API CK-4 engine oil..

Benefits and Applications

- For diesel and gasoline engines
- Exceeds API CK-4, CJ-4, CI-4 / SN
- Excellent cold-crank capabilities
- Helps improve fuel economy

SAE 15W-40 CK-4 Typical Characteristics

Viscosity @ 100°C, cSt	15.9	(ASTM D445-19)
Viscosity Index (VI)	154	(ASTM D2270-16)
Total Base No. TBN	10	(ASTM D2896-15)
Flash Point, COC °C	206	(ASTM D92-18)
Pour Point, °C	-40	(ASTM D97-11)

Available Packaging

18 Liter; 25 Liter, 208 Liter



<https://www.powermerica.net>